

Technical Data:	2750 RXBJ	2750 RXDJ	2750 RXBDJ
Max. working height, ft		90'	
Max. platform height, ft		83'4"	
Max. outreach, ft		51'	
Up and over clearance, ft		35'	
Jib length (jib + basket), ft		8'9"	
Vertical jib rotation		90°	
Turret rotation		± 355°	
Basket rotation		± 41°	
Max. basket load, lbs		550 lbs	
Basket size, ft		4'1" x 2'6" x 3'8"	
Travelling length, ft		24'1" / 21'7"	
Travelling height, ft		7'2"	
Travelling width, ft		4'11" - 3'8"	
Operational width, ft		Wide - Wide 15'1" min. - 17'5" max.	
Stabilizer pad		9" x 17"	
			HYBRID
Diesel engine Kubota D722		14kW/18.8hp	14kW/18.8hp
Fuel tank capacity		6 gal.	6 gal.
Generator		24 V / 22 A	24 V / 22 A
Battery pack	24V/400Ah/5h		24V/200Ah/5h
Transformer	240V only		
Charger	24 V / 30 A		24 V / 30 A
See www.ommelift.com for all features and options			
Gradeability, max. across slope		35% (19.3°)	
Gradeability, max. up and down slope		35% (19.3°)	
Set-up ability on uneven ground		40% (21.8°)	
Crawler track length, ft		6'3"	
Rollers on each side		5	
Total weight, lbs	11,133 lbs	11,133 lbs	11,133 lbs
Live load in transit position	92.0 psf	92.0 psf	92.0 psf
Live load in working position (including max. basket load)	67.2 psf	67.2 psf	67.2 psf
Ground pressure, tracks (Hard surface)	11.0 psi (34.6 psi)	11.0 psi (34.6 psi)	11.0 psi (34.6 psi)
Ground pressure, outrigger	43.6 psi	43.6 psi	43.6 psi
Max. force, outrigger	6836 lbf	6836 lbf	6836 lbf

